



spygas

Flammable Gas Leak Detector

The Spygas range of gas leak detectors are the most technically advanced, simple to use, low cost way of tracing a gas leak.

Ease of use

- One key operation
- Automatic zeroing
- Clear digital display
- Battery level indicator
- Automatic backlight

Loud and clear gas level and audio signal

- Visual gas concentration digital indicator
- 'Geiger Counter' tick at zero gas levels
- 'Crescendo' sounder, rising in pitch with increasing gas concentration

Lightweight and rugged

- 100 grams
- Designed for hand grip
- Pocket sized
- Robust plastic casing





Sensor	Semi-conductor gas sensor - 5 year life span.
Weight	140 g
Dimensions (mm)	Width: 24 (min) 38 (max) Length: 254 Height: 28 (max)
Controls	Single on/off switch
Detection range	50 - 10 000 ppm+ for methane
Display	LCD with nominal 100, 1000 and 10 000 ppm indicators, 5 level battery life indicator and power on indicator.
Back-light	Photo-electric sensor automatically switches display back-light on when ambient light levels are low.
Audio signal	30 second stabilisation indicator. A low frequency tick at 0ppm, increasing in pitch and intensity proportional to gas concentration. Frequency range: 7 Hz - 3 KHz
Battery	2 x AA Alkaline or NiCD/NiMH rechargeable. Alkaline: approx 6 hours continuous use. Rechargeable: approx 3 hours continuous use.
Operating Temperature range	-20 to 50°C 5-95% RH non-condensing
Response time	Less than 5 seconds.
Zeroing	Automatic, microprocessor controlled.
Approval codes	CE marked, EMC: EN50270
Accessories	Protective leather case.
Instructions	Switch on in clean air, wait for 30 seconds then use
Detectable gases	Natural gas, methane, ethane, propane, butane, LPG. A full listing is available on request. A carbon monoxide version is available. Please contact Telegan for details